## dAGE104U40BK-ES

*1U 4-Bay SAS/SATA I/II eSATA JBOD Chassis 350W PSU*

SAS/SATA RAID RoHS Compliant

### Specifications

| | |
|---|---|
| Dimension (W x H x D) | 19 x 1.75 x 22.5 inches |
| Cooling | 4 x 40mm Cooling Fans |
| Color | Black |
| HDD Interface | SAS/ SATA I/II |
| Host Interface | 4 x eSATA Connectors |
| LED Display | LED for Power On/Off, HDD |
| Hot-Swap | Both on Host and Device |
| Material | Heavy-Duty Cold-Roll Steel |
| Power Supply | 350W, Input: 100 to 240 Vac Full Range |

### Features

- Supports Up to 4 SAS/SATA I/II HDDs
- Four eSATA Connections
- LED Indicators for Power and Activity on Each HDD Tray
- 4 Cooling Fans with Status Monitor
- Power + Fan Failure + HDD LED Indicator
- MiniSAS Backplane
- Fully RoHS Compliance

### Recommended Accesories

| Model No. | Description |
|---|---|
| cAGE-4ES2MS | External miniSAS to 4 eSATA Cable |
| cAGE-eSA2eSA | ESATA to ESATA External SATA Cable |

## dAGE104U40BK-PM

*1U 4-Bay SAS/SATA I/II eSATA Port Multiplier JBOD Chassis 350W PSU*

SAS/SATA RAID RoHS Compliant Cooling Fan

### Specifications

| | |
|---|---|
| Dimension (W x H x D) | 19 x 1.75 x 22.5 inches |
| Cooling | 4 x 40mm Cooling Fans |
| Color | Black |
| HDD Interface | SAS/ SATA I/II |
| Host Interface | 1 x eSATA (Port Multiplier) Connector |
| LED Display | LED for Power On/Off, HDD |
| Hot-Swap | Both on Host and Device |
| Material | Heavy-Duty Cold-Roll Steel |
| Material of Main Chassis | Zinc-Plated with Bright Chromate |
| Power Supply | 350W, Input: 100 to 240 Vac Full Range |

### Features

- Supports Up to 4 SAS/SATA I/II HDDs
- eSATA Connection with Port Multiplier Support
- LED Indicators for Power and Activity on Each HDD Tray
- 4 Cooling Fans with Status Monitor
- Power + Fan Failure + HDD LED Indicator
- MiniSAS Backplane
- Fully RoHS Compliance

### Recommended Accesories

| Model No. | Description |
|---|---|
| cAGE-eSA2eSA | ESATA to ESATA External SATA Cable |